3.95/**5**5 QUIZ #2



Exam File Provided By The **UofS IEEE Student Branch**

ieee.usask.ca

Name: Kyle Ness

- 40 Minutes, No materials allowed. (N	<u>umber</u>) indi		_		
For each, indicate where data comes from. Provide the type of addressing mode. Assume that $[X] = 0200_{16}$. (0.4)					
3) LDAA #\$2D. Imme diata addres	ssing. Dat	a come	3 directly	+ron	1 program.
& LDAA \$7C. Direct addressing	. Dota con	ies from	me mory low	oati	on 00 764
c) LDAA \$57BB. Extende & Address	sing. Dota	conest	TOM MEMOR	4/00	ation 578
d) LDAA \$3F, X. Indexed address	· 1			<i>'</i> .	1 1
Calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the offset byte portion of the calculate the value of the calculate the calculate the value of the calculate the		tion. (<u>1</u>)			
0310+5b= 0378 We w	e ways	0370 S	ΓART 1		SBA
	ewayso 1:ments4	0371			BEQ \$031D
FF-56+1=[AA]/ comp	· · ·		ND 3		STAA \$50 WAI
		5070 2			
Show how the JSR instruction can be replaced	by a BSR instr	uction with	appropriate off	set. Th	e op code for
BSR is 8D. (1)	C100 MA	TAT	06.46		IDAA ¢AC
OCD POLY takes 2 by tes so all	C100 MA C102		96 A6 BD C1 60		LDAA \$A6 JSR \$C160
5 program lines will be moved	C102		97 A7		STAA \$A7
beet by 10 your land la Rome			3E		WAI
back by 1 so we want to Braze	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		•		
to location C15F.			•		
GOT CINIL - FO) C160 SHI	FT	44		LSRA
CISE-0104 = 5B TON CO	C161		44		LSRA
180 3B	C162		39		RTS
TC2 common / c return address					
When the MPU executes a (\sqrt{15R com})	1		(Recommendation	HS.	on the
(Stack), jumps to the (Sub					
the end of the (Subtaiting) the (RTS command) causes the MPU to take the					
(Teturn address) off the (Stack), place it back in the (program counter), and					
	,, h	c it buck i	. 4.0 (U	//
continue execution of the main program. (1)					
Describe two ways to halt execution of a program	n in MC68HC1	1. <u>(0.6)</u>	Γ -		
WAI command will hat the	e execu	4100 C	it aprog	ra	m.
. U. 7 Smasning the MC68HUN WY	th a harnmen	willh	alt exec	wio	as well.
★ -			امسمسط النسب	h to fo	-, · · · ·
Consider the following instruction sequence. Determine where the program will branch to for each of the					
following values of unsigned data in memory lo	ation 0050. (<u>1.</u>	<u> </u>			
B(Ba) 95. <u>C607 + D6 = [C6D]</u>	<u>)</u>	1	CART 96		LDAA \$50
V49(b) B7. C609 + 6B = C674	3	C602	43		COMA
		C603			CMPA #\$48
. VGF(c) E1. <u>C607 + D6= [C6DD]</u>		C605			BHI \$????
		C607			BEQ \$????
		C609	2() 6B	BRA \$????

THE END

Department of Electrical Engineering, University of Saskatchewan